



BRIDA AC SO DIN PN-10-16-25-40



ISO 7005 - 2 : 1988 (E)

N- NUMERO DE PERFORACIONES

Diámetro Nominal		PN (ISO) -10			PN (ISO) -16			PN (ISO) -25			PN (ISO) -40		
MM	Pulg.	A	B	N	A	B	N	A	B	N	A	B	N
40	1, 1/2	110	19	4	110	19	4	110	19	4	110	19	4
50	2	125	19	4	125	19	4	125	19	4	125	19	4
65	2, 1/2	145	19	4	145	19	4	145	19	4	145	19	4
80	3	160	19	8	160	19	8	160	19	8	160	19	8
100	3	180	19	8	180	19	8	190	23	8	190	23	8
125	5	210	19	8	210	19	8	220	28	8	220	28	8
150	6	240	23	8	240	23	8	250	28	8	250	28	8
200	8	295	23	8	295	23	12	310	28	12	320	31	12
250	10	350	23	12	355	28	12	370	31	12	385	34	12
300	12	400	23	12	410	28	12	430	31	16	450	34	16
350	14	460	23	16	470	28	16	490	34	16	510	37	16
400	16	515	28	16	525	31	16	550	37	16	585	40	16
450	18	565	28	20	585	31	20	600	37	20	610	40	20
500	20	620	28	20	650	34	20	660	37	20	670	43	20
600	24	725	31	24	770	37	20	770	40	20	795	49	20
700	28	840	31	24	840	40	24	875	43	24	900	49	24
800	32	950	34	24	950	43	24	990	49	24	1030	49	24
900	36	1050	34	28	1050	47	28	1090	49	28	1140	56	28
1000	40	1060	37	28	1170	50	28	1210	56	28	1250	56	28

Dirección: Miguel de Atero 2858 - Quinta Normal - Santiago

Fono/Fax: (2) 774 33 74 - 772 01 42 - 786 79 67

ventas@fluimat.cl - www.fluimat.cl

